

扫码收银 · 感应支付 · 25cm 远距识别

XL-680 桌面扫码支付平台

XL-680 Desktop Scan & Payment Platform

智能扫码收银

CMOS 640×480

≥ 5 mil

100 FPS

71° × 60°

USB 即插即用

01 智能扫码收银 + 感应支付

Scan Checkout & Inductive Payment

收银台一站式扫码，付款码与商品码同一台设备完成。

One device handles payment codes and product barcodes at the checkout.

02 约 25cm 远距识别

Approx. 25 cm Long-Range Reading

顾客付款码远距离即可快速识别，收银更高效。

Swiftly recognises payment QR codes from around 25 cm away.

03 智能感应补光

Smart Induction Lighting

条码、二维码轻松识别，弱光环境同样稳定。

Smart induction lighting keeps barcodes and QR codes readable in low light.

04 角度可调 + 蜂鸣提示

Adjustable Angle & Buzzer

扫描角度可自由调节，蜂鸣提示 + 指示灯反馈收款结果。

Freely adjustable scanning angle with buzzer and indicator feedback for every payment.



正面扫码窗口 (Front View)



角度可调结构 (Adjustable Angle)



合盖侧面 (Closed Side View)

应用场景 Application Scenarios

商超收银台、便利店、餐饮门店、药店、生鲜果蔬店、自助收银等场景；支持微信 / 支付宝等主流付款码识别，收款即扫即得。

Ideal for supermarket checkout, convenience stores, restaurants, pharmacies, fresh food stores and self-checkout. Reads mainstream payment QR codes (WeChat Pay / Alipay) instantly at the counter.

产品特点 Product Features

- **智能扫码收银 + 感应支付**，收银台一站式扫码
Intelligent scan cashier & inductive payment in one device
- **蜂鸣提示**：收款结果声音提示，更安心
Buzzer alarm prompt for safer, more reassuring payment collection
- **即插即用**：兼容 Linux / Android / Windows / iOS
Plug and play, compatible with Linux, Android, Windows and iOS

物理参数 / PHYSICAL

尺寸 Size	135 × 82 × 82 mm
重量 Weight	120 g
线材长度 Cable	1.2 米 1.2 m
接口 Interfaces	USB
工作电压 Voltage	DC 5V (±5%)
扫描提示 Scan prompt	指示灯 + 蜂鸣器 Indicator light + buzzer

性能参数 / PERFORMANCE

图像传感器 Sensor	CMOS 640 × 480, 100 FPS
识读精度 Precision	≥ 5 mil
光源 Light source	白光 LED White LED
扫描角度 Scanning angle	71° (H) × 60° (V) Pitch ±55°, Skew ±55°, Roll 360°
打印对比度 Print contrast	≥ 20%
识读景深 Depth of field	25 ~ 250 mm (支付宝付款码 / Alipay payment QR code) 35 ~ 145 mm (EAN-13, 13 mil)

- **约 25cm 远距识别**：顾客付款码远距离即可快速识别
Swiftly recognizes payment QR codes even at approx. 25 cm
- **智能感应补光**：条码、二维码轻松识别
Smart induction light easily recognizes barcodes & QR codes
- **扫描角度可自由调节**，适配不同收银台高度
Adjustable scanning angle to fit different counter heights

解码类型 / DECODING TYPES

一维码 1D code	EAN-13, EAN-8, UPC-A, UPC-E, ISBN, ISSN, Code 128, Code 39, Code 93, Codabar, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5, Code 11, GS1 Databar, MSI Plessey, Pharma code, Telepen, Trioptic code, Postal Code
二维码 2D code	QR Code, PDF417, Data Matrix, AZTEC

环境参数 / ENVIRONMENTAL

工作温度 Operating temperature	-20°C ~ +50°C
储存温度 Storage temperature	-40°C ~ +70°C
湿度 Humidity	5% ~ 95% (无凝结 / non-condensing)
抗跌落 Shock resistance	可承受 1.5 米跌落 Designed to withstand 1.5 m drops
环境光 Ambient light	0 ~ 100,000 Lux

规格如有更改，恕不另行通知 / Specifications subject to change without notice.